



### Main

Range of product	Trend
Product or component type	Dimmer
Dimmer type	Transistor
Colour tint	White
Quantity per set	1 piece

### Complementary

Wiring device mounting	Flush
Switch function	1-pole 2-way
Dimmer control	Rotary push type
Rated current	10 A, 230 V AC
Power range	Electronic transformer: 60...630 W) 230 V AC halogen lamp: 60...600 W) Incandescent lamp: 60...630 W)
Connections - terminals	Screw terminals
Number of loop terminals	1
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm <sup>2</sup> solid stranded 1 x 1.5...2 x 2.5 mm <sup>2</sup> solid
Material	PC/ABS
Protection type	Short-circuit and overload protection with automatic reset
Embedding depth	29 mm
Height	82 mm
Width	82 mm
Projecting depth	22 mm

### Environment

Standards	EN 60669-1 EN 60669-2-1
Product certifications	CE FIMKO NEMKO SEMKO
IP degree of protection	IP20

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company Schneider Electric. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.