



### Main

Range	Linergy
Product name	BW
Product or component type	Busbar
Busbar description	Insulated bar

### Complementary

Range compatibility	Prisma - P Prisma - G
Poles description	4P
Busbar position	Rear
Installation direction	Vertical
Installation description	Wall-mounted enclosure: 600 mm Floor-standing enclosure: 600 mm Cubicle: 650 mm
[Ui] rated insulation voltage	750 V
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	400 A
[Icw] rated short-time withstand current	20 kA (1 s)
[Ipk] rated peak withstand current	52.5 kA
I <sup>2</sup> t on activation	400000 kA <sup>2</sup> .s
Permissible current	400 A
Length	1000 mm
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm

### Environment

IP degree of protection	IPxx B
Standards	IEC 61439-2
Product certifications	ASEFA KEMA

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0807 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available <a href="#">Download Product Environmental</a>
Product end of life instructions	Need no specific recycling operations