



### Main

Range of product	PrismaG
Product or component type	Door
Type of front cover	Transparent
Provided equipment	Handle Keylock (key 405)
Quantity per set	Set of 1

### Complementary

Door opening side	Reversible
Key number	405
Installation description	Wall-mounted enclosure : 600 mm
Number of vertical modules (50 mm)	9
Special colour options	Yes
Height	480 mm
Width	600 mm
Colour	White RAL 9001

### Environment

IP degree of protection	IP43
IK degree of protection	IK08 conforming to EN/IEC 62262
Standards	EN/IEC 61439-1

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0818 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available <a href="#">Download Product Environmental</a>
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.