

Fuse plug - ST-SILED 24-UK 4 - 0921037

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Fuse plug, Nominal current: 6.3 A, Length: 33.1 mm, Width: 6.1 mm, Height: 26.5 mm, Color: black

The illustration shows the version without LED/light indicator

Key commercial data

package_quantity	50
GTIN	4017918010294

Technical data

General

Note	If the fuse is defective, the downstream circuit is not off load
Color	black
Insulating material	PA
Inflammability class according to UL 94	V2

General

Fuse	G / 5 x 20
Insulating material group	CTI 600
Nominal current I_N	6.3 A
Nominal voltage U_N	24 V

Dimensions

Width	6.1 mm
Length	33.1 mm
Height NS 35/7,5	26.5 mm

classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149

Fuse plug - ST-SILED 24-UK 4 - 0921037

classifications

eCl@ss

eCl@ss 8.0	27141149
------------	----------

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC002018


UNSPSC


UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409


approvals

CSA / UL Recognized / cUL Recognized / GOST / GOST / cULus Recognized /

Approval details

	
Nominal voltage UN	300 V
Nominal current IN	10 A
mm ² /AWG/kcmil	

	
Nominal voltage UN	300 V
Nominal current IN	6.3 A
mm ² /AWG/kcmil	

	
Nominal voltage UN	300 V
Nominal current IN	6.3 A

Fuse plug - ST-SILED 24-UK 4 - 0921037

approvals

mm ² /AWG/kcmil	



accessories

Documentation

ST-IL - 3039900



Drawings

© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>