



Main

Range of product	Opale
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Nb of 18 mm modules per row	13
Nb of horizontal rows	3
Provided equipment	Terminal block support (2) Earth/Neutral terminal block (2) Blanking plate (3) Marking kit (3)
Width	252 mm
Height	485 mm
Depth	111 mm

Complementary

Enclosure mounting	Surface
Total number of 18 mm modules	39
Number of plates	15 for 18 mm dividable
[In] rated current	90 A
Type of rail	DIN
Cable entry	4 knock-outs
Comb busbar and distribution block compatibility	XE compatible
Number of terminal blocks	2 neutral / earth terminal block with 22
Distribution block outgoing	22 x 16 mm ² for earth / neutral 20 x 10 mm ² for earth / neutral 2 x 25 mm ² for earth / neutral
Locking options description	1 keylock + 1 key
Enclosure material	Self-extinguishing material
Colour	Enclosure : white (RAL 9003)

Environment

Standards	IEC 60439-3 IEC 60529 IEC 60695-2-11 IEC 62262
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP30 conforming to IEC 60529 IP30 conforming to EN 60529
IK degree of protection	IK07 conforming to IEC 62262 IK07 conforming to EN 50102

Contractual warranty

Period	18 months
--------	-----------