



Main

Range of product	Prisma Plus System G
Range	Prisma
Product name	G
Product or component type	Duct
Enclosure type	Empty enclosure
Enclosure mounting	Surface
Type of front cover	Without
Number of vertical modules (50 mm)	27
Number of 18 mm modules per row	10

Complementary

Installation description	Floor-standing duct : 300 mm
[Ui] rated insulation voltage	1000 V on main rear busbars conforming to IEC 61439-2
[In] rated current	630 A at 40 °C conforming to IEC 61439-2
[Icw] rated short-time withstand current	25 kA (1 s) conforming to IEC 61439-2
[Ipk] rated peak withstand current	53 kA conforming to IEC 61439-2
Network frequency	50/60 Hz
Number of 9 mm pitches per row	20
Enclosure material	Enclosure : painted sheet steel
Additional information	Can be combined side by side and one on top of another
Height	1530 mm
Width	300 mm
Depth	205 mm
Colour	White RAL 9001

Environment

IP degree of protection	IP43 with door, canopy and IP43 gasket IP31 with door and canopy IP30 with door IP30 without door EN/IEC 60529
IK degree of protection	IK08 with door IK07 without door EN/IEC 62262
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Standards	IEC 62208 IEC 61439-2

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0823 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Need no specific recycling operations