



MODEL NO.

11-12144-A2

PRODUCT LINE

GO Switch Leverless Limit Switches

SPECIFICATIONS

Model 11- 1-1/2" square x 4-9/16" overall
Contact Form SPDT (Form C) contacts;
 10A/120VAC,3A/24VDC
Sensing Range Extended sensing - approx. 14mm (9/16") side sensing
Outlet Position 1/2" NPT conduit outlet behind sensing area
Enclosure Material Stainless steel - corrosion resistant coating (polyurethane)
Approvals CSA / FM explosion proof - CI I, Div 1; Grps A-D; CI II, Div 1, Grps E-G; CI III; (Lead seal req'd within 18")
Wiring Options PVC Lead Wires - 18 gauge - 914mm (36")
Operating Temps* -40 °C to 105 °C

4 Wire PVC & HiTemp Leads

| | |
|-----|-------|
| N/C | Red |
| N/O | Blue |
| COM | Black |
| GND | Green |



Terminations A & F

S-K025 Rev. 4, 0406-5M

Current as of Aug 1, 2015 - subject to change without notice.

TOPWORX

TopWorx
 3300 Fern Valley Rd.
 Louisville, KY 40213

(502) 969-8000 ph.
 (502) 969-5911 fax
 www.topworx.com